

深圳仪普生科技有限公司

SHENZHEN EPELSA TECHNOLOGIES LIMITED

Http://www.eplsa.cn

TEL: 400-6615-016



GRUPO EPELSA

MARTE 10 V4 IC

Technical Information

Capacity	6kg	15kg	30kg	6/15kg	15/30kg	12kg (6.000d)	30kg (6.000d)
Division	2g	5g	10g	2/5g	5/10g	2g	5g
Minimum Load	40g	100g	200g	40g	100g	40g	100g
Maximum Tare	3.000g	9.995g	9.990g	3.000g	9.995g	3.000g	9.990g

Main



Low-consumption, interconnected retail scale with a thermal receipt printer. Automatic repositioning to Zero, Zero key, Possibility to print under minimum load according to the calibration standards.
Send of the weight over the plate under petition.
Four seller keys scale with thermal printer, two working modes:
1. - NETWORK: interconnected through cable (RS-485) to other scales. In the interconnection with ILC scales, these must be with the lower number.
2.- LOCAL: Independent

Display



LCD indication display with 5 digits for WEIGHT, 6 digits for PRICE, and 7 digits for AMOUNT. TARE indication, "price x kg" indication, "price x 100 g" indication, energy saving deactivated indication, open vendor indicator, battery level indicator, zero weight, stability, net weight.

Keyboard



49-key keyboard, 16 direct PLUs and 33 function keys.
Possibility of programming 16 semi-direct items for quick PLU access, 4 active vendors, disconnection key.
New Keys functionality:

- F1: Items programming.
- F2: Keys Programming.
- F3: Items listing.
- X: Absolute grand total, VAT and time.
- Z: Absolute grand total, VAT, time and absolute grand total erasure.
- GA: Items grand total
- GV: Salesclerks grand total – Saleclerk total (If only one saleclerk has sales).
- GI: VAT grand total.

Programmable PLU Data

Item price, 25-character product description, PLU type, "price x kg" or "price x 100g", family, direct key, assigned tare, sale mode (by weight or unit), and internal code.

Memory

8032 Microprocessor, up to 2000 price PLUs, 25 characters for item text, storage of daily sales, accumulated sales, etc.

Thermal Receipt Printer



Thermal receipt printer with continuous paper. Choice of fonts, up to 3 lines for the programming of headings and one for legends.

Interface	Interconnection with up to 8 scales via RS-485, option for connection to a scanner and a cash drawer. Connection to the HOST through serial cable RS-232
Features  	<p>Internal battery of 6V, 10A, external charging of 12V, 500mA, and an optional 12V external battery.</p> <p>Price and functions change to work in constant, addition, subtraction, multiplication product, total, sub-total and grand-total mode.</p> <p>Sale statistics for absolute big total, accumulated total, by vendor, by family, by PLUs, etc.</p> <p>Different methods of payment, transaction review and cancellation, receipt reprinting, headings and legends programming, bar codes, VAT, receipt burn intensity, summary receipt, etc.</p>
Operating Temperature	-10° a +40°C
Voltage	12 V, 500 mA external adaptor 6 V, 10 A internal battery 12 V external battery connection
Current Consumption	Between 0.5 y 12w
Frequency	50 / 60 HZ